Specifications for non linear Low Profile LED Lightbar

Quantity of 7

Dimensions – 43.7” Length, 19.8” depth, 1.96” height, weight 39.3lbs

Reverse V shaped to the front and straight across in rear

Hook mount

Warranty – 5 year std warranty on all LED components, 1 year on labor

Dual color LEDs – Blue and white on the front, blue and amber on the rear

High brightness LEDs with offset, compound-curve, polished reflector

Dimming

Operating temperature range of -40F to 149F

22 LED section with 2 alley lights

Specifications for Internal LED light system

Quantity of 1

Spectralux Multi color LED technology configurable of blue and white

Solaris LED assemblies for the highest optical efficiency

ROC (reliable onboard circuity)

Compatible with FS convergence network siren

Split front model with 8 LED reflectors

Twenty six (26) flash pattererns

Standard five year warranty parts/ one year factory labor warranty

12.8 VDC

Operating temperature -30c to +65 c

Amp draw total split front headliner – 8 amps

Specifications for remote head siren controller with PA mic.

Quantity of 8

Electronic siren and light control combined

Functions programmable at point of installation

Easy action rubberized push-buttons

3 position slide switch control

Standard siren tones – Wail, Yelp, Hi-Lo priority, Air Horn and Manual

Radio rebroadcast and PA

Dimensions- Control head- H x L x D 3.1” x 6.8” x 1.3”, Amplifier- 2.3” x 6.3” x 6.4”

Audio Power-45W in PA mode

Standby Current – 0.5 amps

Operating Temp - -30C to +65C

Frequency Range – 700-1500Hz

Input Voltage – 11-16VDC

Voltage Output – 62-66 Vrms peak to peak

Output Impedance (PA) – 4000 ohms nominal

Auto Response – 300-3000 Hz+/- 3dB

Siren Speaker and speaker mount

Quantity of 8

Features Neo-driver

100 watt high-output power

Black, corrosion-resistant aluminum housing

Sound output meets SAE J1849 and Class A

5.9”W x 5.5”H x 2.7”D

5.5lbs

Speaker mount for 4 2014 Dodge Charger and 4 2015 Ford Police Utility Interceptors